

DATA SHEET

Stonehenge LVT Click Flooring



Technical Specification:

Total Thickness	EN-ISO 24346	5mm
Wear Layer Thickness	EN-ISO 24340	0.5mm
Size		600mm x300mm
Domestic Use	EN-ISO 10874	Class 23
Commercial Use	EN-ISO 10874	Class 33
Light Industrial Use	EN-ISO 10874	Class 42
Total Weight	ISO 23997	8300g/m2 ± 5%
Wear Layer Binding Content	EN-ISO 10582	Class 1
Dimensional Stability	EN-ISO 23999	0.05%
Straightness, Squareness	EN-ISO 24342	<400mm <0.25mm / >400mm <0.35mm
Slip Resistance	DIN 51130	R 10
Castor Chair	ISO 4918	Pass
Colour Fastness	EN ISO 105-B02	≥ 6
Resistance to Chemicals	EN-ISO 26987	Very Good
Acoustic Properties	EN-ISO 717-2	Up to 15db with 2mm Underlay
Indoor Air Emission	EN 16516	≤ 0.02 mg/m3
Recyclable Content	Up to 60% in backing material	
Reaction to Fire	EN 13501-1	Bfl-s1, L, NCS with and without underlay
Thermal Conductivity	EN 12524	0.25 W/mK
Body Voltage	EN 1815	≤ 2.0 kV
Warranty	10 Years Residential / 7 Years Commercial	

PHTHALATE FREE . FLOOR SCORE . 100% STABILITY . NO EXPANSION . NO CONTRACTION

